

GenSet



MG 10000 S-R



GEN SET S.p.a.

Via Stazione,5 - 27030 Villanova D'Ardenghi (Pavia) Italy

Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244

E-mail: genset@genset.it - internet: [//www.genset.it](http://www.genset.it)

**SILENCED POWER GENERATOR
OUTPUT POWER 8,25 KVA SINGLE-PHASE
DIESEL ENGINE 3000 RPM**

Standard Features	+ 12 V built-in battery + 1 x 230V - 32A EEC three-phase socket + 1 x 230V - 16A EEC three-phase socket + Foreseen for AMF-ATS or Remote control operation + Power output protection + Power output protection + Earth Leakage Circuit Breaker + Voltmeter + Hourmeter + Central lifting eye
Options available as factory options	+ Versions with different voltages
Accessories on request	+ Trolley: two wheels and handles + AMF/ATS panel for auto start operation + Remote Start/Stop kit by cable (20 m)
Noise level	+ Lwa 97 (72 dB at 7 m)
AC generator 50Hz	+ Type: synchronous + Single-phase power (stand-by): 9,4kVA - 230V + Single-phase power (prime): 8,4kVA - 230V + Power factor: $\cos \phi$ 0,8
Diesel Engine 3000 rpm	+ Type: Lombardini 25LD330/2 - 2 cyl. - 654 cm³ + Max power: 12,6 hp (9,3 kWm) + Starting system: electric (12Vdc) + Cooling system: air + Fuel consumption @ 75%: 2,2 l/h
Other features	+ Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 m (*) + Mechanical Protection: IP 23 + Fuel tank capacity: 10,5 l + Dimensions (L x W x H): 1000 x 560 x 715 mm + Dry weight: 190 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.

In line with our continued development, innovation and voice of costumer program, we reserve the right to change data without notice.