



## **GEN SET S.p.a.**

Via Stazione,5 - 27030 Villanova D' Ardenghi (Pavia) Italy Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244 E-mail: genset@genset.it - internet://www.genset.it



## SUPER SILENCED POWER GENERATOR OUTPUT POWER 10 KVA SINGLE-PHASE DIESEL ENGINE 3000 RPM

| Standard Features                           | + Auto engine protection shutdown system with warning lights for:  - battery charger failure  - high water temperature  - low fuel level  - low oil pressure  + 12 V built-in battery  + 1 x 230V - 32A EEC single-phase socket  + 1 x 230V - 16A EEC single-phase socket  + Power output protection  + Earth leakage circuit breaker  + Fuel level gauge  + Voltmeter  + Hourmeter  + Central lifting eye |
|---|--|
| <b>Options</b> available as factory options | + Versions with different voltages + 60Hz version + Spark arrester muffler + Engine heater + Foreseen for AMF-ATS or Remote control operation  |
| Accessories on request                      | + Trolley: two wheels and handles<br>+ AMF/ATS panel for auto start operation<br>+ Remote Start/Stop kit by cable (20 m)   |
| Noise level                                 | + Lwa 95 (70 dB at 7 m)  |
| AC generator - 50Hz                         | + Type: synchronous<br>+ Single-phase power (stand-by): 10kVA - 230V<br>+ Single-phase power (prime): 9kVA - 230V<br>+ Power factor: cos φ 0,8   |
| Diesel Engine<br>3000 rpm                   | + Type: Kubota D722 - 3 cyl 719 cm <sup>3</sup><br>+ Max power: 19 hp (14 kWm)<br>+ Starting system: electric (12Vdc)<br>+ Cooling system: water<br>+ Fuel consumption @ 75%: 3,3 l/h  |
| Other features                              | + Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 m (*) + Mechanical Protection: IP 23 + Fuel tank capacity: 30 l + Dimensions (L x W x H): 1050 x 630 x 775 mm + Dry weight: 295 kg   |