

GenSet



MG 10 I-SY



GEN SET S.p.a.

Via Stazione,5 - 27030 Villanova D'Ardenghi (Pavia) Italy

Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244

E-mail: genset@genset.it - internet: [//www.genset.it](http://www.genset.it)

**SILENCED POWER GENERATOR
OUTPUT POWER 11 KVA THREE-PHASE AND 3,6 KVA SINGLE-PHASE
DIESEL ENGINE 1500 RPM**

Standard Features	+ Auto engine protection shutdown system with warning lights in case of: - battery charger failure - low fuel level - low oil pressure - high water temperature + 1 x 32A, 400V three-phase EEC socket + 1 x 32A, 230V single-phase EEC socket + 12V built-in battery + Hourmeter + Voltmeter + Emergency stop button + Fuel level visual indicator + Foreseen for AMF-ATS or Remote control operation + Earth leakage circuit breaker + Power output protection + Engine oil drain pipe + Central lifting eye
Options available as factory options	+ Versions with different voltages + 60Hz version + Spark arrester muffler + Automatic voltage regulator
Accessories on request	+ Quadro per avviamento automatico (AMF/ATS) + Remote Start/Stop kit by cable (20 m)
Noise level	+ Lwa 89 (64 dB at 7 m)
AC generator - 50Hz	+ Type: synchronous + Three-phase power (stand-by): 11kVA - 400V + Three-phase power (prime): 10kVA - 400V + Single-phase power (max.): 3,6kVA - 230V + Power factor: cos ϕ 0,8
Diesel Engine 1500 rpm	+ Type: Yanmar 3TNV76 - 3 cyl. - 1116 cm³ + Max power: 12,1 hp (9 kWm) + Starting system: electric (12Vdc) + Cooling system: water + Fuel consumption @ 75%: 2 l/h
Other features	+ Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 m (*) + Mechanical Protection: IP 23 + Fuel tank capacity: 40 l + Dimensions (L x W x H): 1650 x 700 x 980 mm + Dry weight: 395 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.

In line with our continued development, innovation and voice of costumer program, we reserve the right to change data without notice.