

# GenSet



## MG 16 I-SY



**GEN SET S.p.a.**

Via Stazione,5 - 27030 Villanova D'Ardenghi (Pavia) Italy

Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244

E-mail: [genset@genset.it](mailto:genset@genset.it) - internet: [//www.genset.it](http://www.genset.it)

**SILENCED POWER GENERATOR**  
**OUTPUT POWER 17 KVA THREE-PHASE AND 5,6 KVA SINGLE-PHASE**  
**DIESEL ENGINE 1500 RPM**

|                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Standard Features</b>                       | <ul style="list-style-type: none"> <li>+ Auto engine protection shutdown system with warning lights in case of: <ul style="list-style-type: none"> <li>- battery charger failure</li> <li>- low fuel level</li> <li>- low oil pressure</li> <li>- high water temperature</li> </ul> </li> <li>+ 1 x 32A, 400V three-phase EEC socket</li> <li>+ 1 x 32A, 230V single-phase EEC socket</li> <li>+ 12V built-in battery</li> <li>+ Hourmeter</li> <li>+ Voltmeter</li> <li>+ Emergency stop button</li> <li>+ Fuel level visual indicator</li> <li>+ Foreseen for AMF-ATS or Remote control operation</li> <li>+ Earth leakage circuit breaker</li> <li>+ Power output protection</li> <li>+ Engine oil drain pipe</li> <li>+ Central lifting eye</li> </ul> |
| <b>Options</b><br>available as factory options | <ul style="list-style-type: none"> <li>+ Versions with different voltages</li> <li>+ 60Hz version</li> <li>+ Spark arrester muffler</li> <li>+ Automatic voltage regulator</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Accessories on request</b>                  | <ul style="list-style-type: none"> <li>+ Quadro per avviamento automatico (AMF/ATS)</li> <li>+ Remote Start/Stop kit by cable (20 m)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Noise level</b>                             | + Lwa 90 (65 dB at 7 m)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>AC generator - 50Hz</b>                     | <ul style="list-style-type: none"> <li>+ Type: synchronous</li> <li>+ Three-phase power (stand-by): 17kVA - 400V</li> <li>+ Three-phase power (prime): 15,3kVA - 400V</li> <li>+ Single-phase power (max.): 5,6kVA - 230V</li> <li>+ Power factor: cos <math>\phi</math> 0,8</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Diesel Engine 1500 rpm</b>                  | <ul style="list-style-type: none"> <li>+ Type: Yanmar 3TNV88 - 3 cyl. - 1642 cm<sup>3</sup></li> <li>+ Max power: 18,1 hp (13,5 kWm)</li> <li>+ Starting system: electric (12Vdc)</li> <li>+ Cooling system: water</li> <li>+ Fuel consumption @ 75%: 2,7 l/h</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Other features</b>                          | <ul style="list-style-type: none"> <li>+ Insulation Class: H</li> <li>+ Ambient temperature: 40 °C (*)</li> <li>+ Altitude: 1000 m (*)</li> <li>+ Mechanical Protection: IP 23</li> <li>+ Fuel tank capacity: 40 l</li> <li>+ Dimensions (L x W x H): 1650 x 700 x 980 mm</li> <li>+ Dry weight: 445 kg</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                         |

(\*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.

In line with our continued development, innovation and voice of costumer program, we reserve the right to change data without notice.