

GenSet



MG 5000 I-Y/E



GEN SET S.p.a.

Via Stazione,5 - 27030 Villanova D'Ardenghi (Pavia) Italy

Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244

E-mail: genset@genset.it - internet: [//www.genset.it](http://www.genset.it)

**POWER GENERATOR
OUTPUT POWER 4 KVA SINGLE-PHASE
DIESEL ENGINE 3000 RPM**

Standard Features	+ Low oil pressure and battery charger warning lights + 12 V built-in battery + 2 x 230V single-phase Schuko sockets + 12Vdc battery charger outlet + Power output protection + Wheels and handles
Options available as factory options	+ Versions with different voltages + 60Hz version
Accessories on request	+ Not available
Noise level	+ Lwa 100 (75 dB at 7 m)
AC generator 50Hz	+ Type: synchronous + Single-phase power (max.): 4kVA - 230V + Battery charger: 120W - 12V - 10A - DC + Power factor: $\cos \phi$ 0,8
Diesel Engine 3000 rpm	+ Type: Yanmar L70N - 1 cyl. - 320 cm³ + Max power: 6,1 hp (4,5 kWm) + Starting system: electric (12Vdc) + Cooling system: air + Fuel consumption @ 75%: 1 l/h
Other features	+ Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 m (*) + Mechanical Protection: IP 23 + Fuel tank capacity: 3,3 l + Dimensions (L x W x H): 720 x 460 x 510 mm + Dry weight: 98 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.

In line with our continued development, innovation and voice of costumer program, we reserve the right to change data without notice.